
Interactive intuitionistic fuzzy technique in multi-objective optimization

Abstract: In this paper, an interactive approach in multi objective optimization problem under intuitionistic fuzzy environment is presented. This intuitionistic fuzzy problem is first converted into a single objective crisp optimization problem. In proposed approach, in each step, decision maker (DM) is requested to update the reference acceptance level and reference rejection level of referred objective only. Membership and non-membership grades of all other objectives are automatically updated from the list of trade off rates in each stage. It is repeated until DM is satisfied with the optimal solution. An illustrative numerical example is provided to demonstrate the feasibility and efficiency of the proposed method and conclusions are drawn.

Keywords: interactive technique; fuzzy set; fuzzy optimization; interactive fuzzy optimization; intuitionistic fuzzy sets; intuitionistic fuzzy optimization; multi objective optimization; trade off rates; Pareto optimal solution; decision making under uncertainty.

1 Introduction:

Modeling of most of the real life problems involves multi objective optimization processes that in general have conflicting objectives. And hence solutions of such problems are in general compromise solutions which satisfy each objective function to a degree of satisfaction and concept of belongingness and non-belongingness arises.

Zimmermann (1978) used the fuzzy set that was introduced by L. A. Zadeh (1965) for solving the fuzzy multi objective mathematical programming problem. Optimization in fuzzy environment was further studied and was applied in various areas by many researchers such as Tanaka, Sakawa (1984), Roy (2011) etc. Fuzzy optimization problem are more flexible and allow us to find solutions in more realistic ways than the analogous crisp optimization technique.

Copyright © 200x Inderscience Enterprises Ltd.

Consequently fuzzy set theory has been widely developed and various modifications and generalizations have appeared. One of them is the concept of intuitionistic fuzzy sets, introduced by K. Atanassov (1986). It considers not only the degree of membership but also the degree of non-membership as well.

A fuzzy interactive system was introduced by Sakawa (1984) which supports a decision maker in solving programming models with fuzzy constraints and fuzzy goals. Since the decision maker is involved in solution procedure, the interactive approaches play an important role in deriving the best preferred compromise solution. According to Ji, Shengyue et al. (2009) the main advantage of interactive approaches is that the DM controls the search direction during the solution procedure and, as a result, the efficient solution achieves his/her preferences.

The paper is arranged as follows. Initially few definitions are given. Then fuzzy multi objective programming problem is discussed in short. Next, interactive fuzzy multi objective optimization technique is discussed. Then the proposed method of interactive multi objective optimization technique under intuitionistic fuzzy environment is introduced. This method and algorithm are discussed in detail. One numerical problem is considered and solved using both interactive fuzzy and interactive intuitionistic fuzzy multi objective optimization technique and conclusions are reached.

2 Definitions:

Definition 2.1: A fuzzy subset $\tilde{A}$ of universal set S is defined by its membership function $\mu_{\tilde{A}}: S \rightarrow [0, 1]$ that assigns to every $x \in S$, a real number $\mu_{\tilde{A}}(x)$ in the closed unit interval $[0, 1]$. Here the value of $\mu_{\tilde{A}}(x)$ at x represents the grade of membership of x in $\tilde{A}$. So nearer the value of $\mu_{\tilde{A}}(x)$ is unity, the grade of membership of x is higher in $\tilde{A}$.

Definition 2.2: An intuitionistic fuzzy subset $\tilde{A}^i$ of universal set S is defined as

$$\tilde{A}^i = \{ \langle x, \mu_{\tilde{A}^i}(x), \nu_{\tilde{A}^i}(x) \rangle \mid x \in S \},$$

Interactive intuitionistic fuzzy technique in multi-objective optimization

Where $\mu_{\tilde{A}^i}(x): S \rightarrow [0, 1]$ and $\nu_{\tilde{A}^i}(x): S \rightarrow [0, 1]$ such that $0 \leq \mu_{\tilde{A}^i}(x) + \nu_{\tilde{A}^i}(x) \leq 1$, here $\mu_{\tilde{A}^i}(x)$ and $\nu_{\tilde{A}^i}(x)$ denote the degree of membership and degree of non-membership of x in $\tilde{A}^i$ respectively.

Definition 2.3: Essentially, Pareto optimality describes a state of affairs in which resources are distributed such that it is not possible to improve a single individual without also causing at least one other individual to become worse off than before the change.

A point x^* in X is said to be an Pareto optimal solution, sometimes referred to as M-Pareto optimal solution, to a generalized multi objective linear programming problem if and only if there does not exist another x_1 in X such that $\mu_i(z_i(x_1)) \geq \mu_i(z_i(x^*)) \forall i$ and $\mu_j(z_j(x_1)) \neq \mu_j(z_j(x^*))$ for at least one j .

Definition 2.4: A trade-off is a situation that involves losing one quality or aspect of something in return for gaining another quality or aspect. Trade studies are essentially decision-making exercises.

3 Fuzzy and intuitionistic fuzzy multi objective programming:

In 1978 Zimmermann had extended fuzzy linear programming approach to following multi objective linear programming problem, with k linear objective functions $z_i(x) = c_i x$, $i = 1, 2, \dots, k$ [9] as

$$\min z(x) = (z_1(x), z_2(x), \dots, z_k(x))^T$$

subject to the constraints $Ax \leq b$, $x \geq 0$,

Here $c_i = (c_{i1}, c_{i2}, \dots, c_{in})$, $i = 1, 2, \dots, k$ and $x = (x_1, x_2, \dots, x_n)^T$ and $b = (b_1, b_2, \dots, b_m)^T$ and $A = [a_{ij}]$ is an $m \times n$ matrix.

For each of the objective functions $z_i(x) = c_i x$, with $i = 1, 2, \dots, k$, it is assumed that the DM has a fuzzy goal. Taking one objective function at a time, individual minimum and maximum values are obtained subject to given constraints for each objective function. Then following the fuzzy

A. Garai et al.

decision by Bellman and Zadeh (1970), the original multi objective linear programming problem may be interpreted as

$$\begin{aligned} & \max \min_{i=1,2,\dots,k} \mu_i(z_i(x)) \\ & \text{subject to the constraints } Ax \leq b, x \geq 0, \end{aligned}$$

Here $\mu_i(z_i(x))$ is the membership function of i^{th} objective function for $i = 1, 2, \dots, k$. If an auxiliary variable λ , with $\lambda = \min_{i=1,2,\dots,k} \mu_i(z_i(x))$ is introduced, the conventional linear programming problem is obtained as

$$\begin{aligned} & \max \quad \lambda \\ & \text{subject to } \lambda \leq \mu_i(z_i(x)), i = 1, 2, \dots, k \\ & Ax \leq b, x \geq 0 \end{aligned}$$

For this linear membership function, as suggested by Zimmermann (1978), it can be easily shown that if the optimal solution of the above problem is unique, it is also a Pareto optimal solution of the multi objective linear programming problem.

On the other hand, intuitionistic fuzzy optimization problem was formulated and solved by intuitionistic fuzzy sets over the objectives and constraints by Plamen Angelov in his historic paper in 1997.

4 Interactive fuzzy multi objective optimization technique:

In fuzzy approach to multi objective linear programming problem as proposed by Zimmermann and his successors, it was assumed that the fuzzy decision of Bellman and Zadeh (1970) is the proper representation of the fuzzy preference levels of the decision maker (DM). But according to Masatoshi Sakawa (1990), these approaches are preferable only when the DM feels that the fuzzy decision is appropriate for combining the fuzzy goals and/or constraints; and such situations seem to occur rarely in reality.

Consequently it is evident that an interaction with in optimization process with (by) the DM is necessary. In his famous paper, M. Sakawa (1984)

developed an interactive fuzzy multi objective linear programming method mixing interactive approaches into the fuzzy approaches (assuming that the DM has a fuzzy goal for each of the objective functions).

5 Proposed interactive intuitionistic fuzzy multi objective optimization technique:

In interactive fuzzy multi objective optimization technique, only degree of acceptance of objective function is considered to describe impreciseness. But It is well known from the renowned research by Atanassov in 1995 that when the degree of rejection (non-acceptance) is defined simultaneously with the degree of acceptance (membership) and when both these degrees are not complementary to each other, intuitionistic fuzzy set (IF) can be used as a more general and full tool for describing this impreciseness. Actually, as Angelov mentioned in 1997 that it is sometimes better to represent deeply existing nuances in problem formulation defining objectives and constraints (or part of them) by IF sets. Hence usage of intuitionistic fuzzy set is proposed in interactive optimization technique.

In general, the linear programming problem is represented as the following vector-minimization problem:

$$\begin{aligned} &\text{optimize } z(x) = (z_1(x), z_2(x), \dots, z_k(x))^T \\ &\text{subject to the constraints } Ax \leq b, x \geq 0, \end{aligned}$$

Where $z_1(x), z_2(x) \dots z_k(x)$ are k conflicting linear objective functions.

1. The individual minimum and maximum of objective function $z_i(x) = c_i x$, $i = 1, 2 \dots k$ under given constraints are computed.
2. Taking into account these individual minimum and maximum of each objective function, together with the increase rate of satisfaction in terms of the membership degree and decrease rate of satisfaction in terms of non-membership degree such that sum of membership and non-membership degree does not exceed unity, the DM determines the membership functions $\mu_i(c_i x)$ for each $i =$

1, 2 ...k and non-membership function $\nu_i(c_i x)$ for each $i = 1, 2 \dots k$ in a subjective manner. It is noted that for minimization type objective function, if level of acceptance are 0 and 1 at z_i^0 and z_i^1 respectively for i^{th} objective function $z_i(x) = c_i x$, then corresponding linear membership function may be taken as

$$\mu_i^R(z_i(x)) = \begin{cases} 0 & \text{if } z_i(x) \geq z_i^0 \\ \frac{z_i^0 - z_i(x)}{z_i^0 - z_i^1} & \text{if } z_i^1 \leq z_i(x) \leq z_i^0 \\ 1 & \text{if } z_i(x) \leq z_i^1 \end{cases}$$

and if level of rejection are 1 and 0 at $z_i^{0'}$ and z_i^1 respectively for i^{th} objective function $z_i(x) = c_i x$, then corresponding linear non membership function may be taken as

$$\nu_i^L(z_i(x)) = \begin{cases} 1 & \text{if } z_i(x) \geq z_i^{0'} \\ \frac{z_i^{0'} - z_i(x)}{z_i^{0'} - z_i^1} & \text{if } z_i^1 \leq z_i(x) \leq z_i^{0'} \\ 0 & \text{if } z_i(x) \leq z_i^1 \end{cases}$$

Again for maximization type, if level of acceptance are 0 and 1 at z_i^0 and z_i^1 respectively for i^{th} objective function $z_i(x) = c_i x$, then corresponding linear membership function may be taken as

$$\mu_i^L(z_i(x)) = \begin{cases} 1 & \text{if } z_i(x) \geq z_i^1 \\ \frac{z_i(x) - z_i^0}{z_i^1 - z_i^0} & \text{if } z_i^0 \leq z_i(x) \leq z_i^1 \\ 0 & \text{if } z_i(x) \leq z_i^0 \end{cases}$$

and if level of rejection are 1 and 0 at $z_i^{0'}$ and z_i^1 respectively for i^{th} objective function $z_i(x) = c_i x$, then corresponding linear non membership function may be taken as

$$\nu_i^R(z_i(x)) = \begin{cases} 1 & \text{if } z_i(x) \leq z_i^{0'} \\ \frac{z_i^1 - z_i(x)}{z_i^1 - z_i^{0'}} & \text{if } z_i^{0'} \leq z_i(x) \leq z_i^1 \\ 0 & \text{if } z_i(x) \geq z_i^1 \end{cases}$$

For equality type objective function, both left spade and right spade of that membership function are to be taken. Here 'L' and 'R' denote left and right spade of function respectively.

3. For initial reference membership levels $\hat{\mu} = (\hat{\mu}_1, \dots, \hat{\mu}_k)^T$, usually unity and reference non membership levels $\hat{\nu} = (\hat{\nu}_1, \hat{\nu}_2, \dots, \hat{\nu}_k)^T$, usually zero, the corresponding Pareto optimal solution, if it exists, is obtained by solving the following problem:

$$\text{minimize } \max_{i=1,2,\dots,k} \{\hat{\mu}_i - \mu_i(z_i(x))\}$$

$$\text{minimize } \max_{i=1,2,\dots,k} \{\nu_i(z_i(x)) - \hat{\nu}_i\}$$

$$\text{subject to } Ax \leq b, x \geq 0$$

i.e. equivalently

$$\text{minimize } v$$

$$\text{minimize } w$$

$$\text{subject to } \{\hat{\mu}_i - \mu_i(z_i(x))\} \leq v, i = 1, 2, \dots, k$$

$$\{\nu_i(z_i(x)) - \hat{\nu}_i\} \leq w, i = 1, 2, \dots, k$$

$$Ax \leq b, x \geq 0, v \geq 0, w \geq 0$$

With $v = \max_{i=1,2,\dots,k} \{\hat{\mu}_i - \mu_i(z_i(x))\}$ and $w = \max_{i=1,2,\dots,k} \{\nu_i(z_i(x)) - \hat{\nu}_i\}$. Here

all membership functions $\mu_i(z_i(x))$, $i = 1, 2, \dots, k$ and non-membership functions $\nu_i(z_i(x))$, $i = 1, 2, \dots, k$ are linear, the above problem is linear programming problem.

This two-objective linear optimization problem is then converted into following single objective optimization problem as follows:

$$\begin{aligned}
 & \min \quad v + w \\
 & \text{subject to } \{\hat{\mu}_i - \mu_i(z_i(x))\} \leq v, \quad i = 1, 2, \dots, k \\
 & \quad \quad \quad \{\hat{\nu}_i(z_i(x)) - \nu_i\} \leq w, \quad i = 1, 2, \dots, k \\
 & \quad \quad \quad Ax \leq b, \quad x \geq 0, v \geq 0, w \geq 0
 \end{aligned}$$

4. In order to help the DM express a level of preference for membership and non-membership functions at next level of interaction, DM is first requested to choose an appropriate standing objective function, say $z_i(x)$, among all objectives $z_j(x)$, $j = 1, 2, \dots, k$ and corresponding reference membership level and reference non membership level. For membership function, trade-off information between this standing membership function $\mu_i(z_i(x))$ and each of the other membership functions is analytically computed and similarly for non membership function, trade-off information between standing non membership function $\nu_i(z_i(x))$, corresponding to same objective function $z_i(x)$, and each of the other non membership functions is analytically computed. The reference membership levels and reference non membership levels for other objective functions are obtained from that trade off rates. These trades off rates, for both membership and non membership functions, together with that Pareto optimal solution are then supplied back to DM, as was done by Sakawa in 1998.
5. If the DM is satisfied with the values of objective function together with current membership and non membership levels in that Pareto optimal solution, stop. In that case, the current Pareto optimal solution is the satisfying solution of the DM. Otherwise, the DM is requested to update the current reference membership and non-membership level of only standing objective function $z_i(x)$, by considering the last optimal values of the membership functions and non-membership function together with both trade-off rates and return to Step 3. It should be stressed to

Interactive intuitionistic fuzzy technique in multi-objective optimization

the DM that any improvement of one membership function can be achieved only at the expense of at least one of the other membership functions.

6. Numerical example of interactive intuitionistic fuzzy optimization technique:

Let us consider the following fuzzy linear programming problem:

$$\begin{array}{ll} \text{fuzzy max} & z_1 = 5x_1 + 5x_2, \\ \text{fuzzy min} & z_2 = 5x_1 + x_2, \\ \text{fuzzy max} & z_3 = 3x_1 - 8x_2, \\ \text{subject to} & 5x_1 + 7x_2 \leq 12, \quad 9x_1 + x_2 \leq 10, \quad -5x_1 + 3x_2 \leq 3, \\ & x_1 \geq 0, x_2 \geq 0, \end{array}$$

The problem is solved in steps as follows:

1. The individual minimums and maximums of each objective function $z_i(x) = c_i x$, $i = 1, 2, 3$ under the given constraints are computed and obtained as in Table 1.
2. Assume that the DM specifies the corresponding sub intervals as given in Table 2. Then linear membership and linear non membership functions are taken as follows:

$$\begin{aligned} \mu_1^L(z_1(x)) &= \begin{cases} 1 & \text{if } z_1(x) \geq 10 \\ \frac{z_1(x)-0}{10} & \text{if } 0 \leq z_1(x) \leq 10, \\ 0 & \text{if } z_1(x) \leq 0 \end{cases}, \quad \nu_1^R(z_1(x)) = \begin{cases} 1 & \text{if } z_1(x) \leq -2 \\ \frac{10-z_1(x)}{12} & \text{if } -2 \leq z_1(x) \leq 10 \\ 0 & \text{if } z_1(x) \geq 10 \end{cases} \\ \mu_2^R(z_2(x)) &= \begin{cases} 0 & \text{if } z_2(x) \geq 6 \\ \frac{6-z_2(x)}{5} & \text{if } 1 \leq z_2(x) \leq 6, \\ 1 & \text{if } z_2(x) \leq 1 \end{cases}, \quad \nu_2^L(z_2(x)) = \begin{cases} 0 & \text{if } z_2(x) \leq 1 \\ \frac{z_2(x)-1}{7} & \text{if } 1 \leq z_2(x) \leq 8 \\ 1 & \text{if } z_2(x) \geq 8 \end{cases} \end{aligned}$$

$$\mu_3^L(z_3(x)) = \begin{cases} 1 & \text{if } z_3(x) \geq 0 \\ \frac{z_3(x)+10}{10} & \text{if } 0 \leq z_3(x) \leq 10, \\ 0 & \text{if } z_3(x) \leq -10 \end{cases}, \quad \nu_3^R(z_3(x)) = \begin{cases} 1 & \text{if } z_3(x) \leq -12 \\ \frac{0-z_3(x)}{12} & \text{if } -12 \leq z_3(x) \leq 0 \\ 0 & \text{if } z_3(x) \geq 0 \end{cases}$$

3. Suppose that, DM takes unity as initial reference membership levels for z_i i.e. $\hat{\mu}_i = 1, \forall i$ and zero as initial reference non membership levels for z_i i.e. $\hat{\nu}_i = 0, \forall i$. Then the corresponding minimax problem is obtained as

$$\begin{aligned} & \min \{ \max(1 - \mu_1(z_1), 1 - \mu_2(z_2), 1 - \mu_3(z_3)) \} \\ & \max \{ \min(\nu_1(z_1) - 0, \nu_2(z_2) - 0, \nu_3(z_3) - 0) \} \\ & \text{subject to } 5x_1 + 7x_2 \leq 12, \quad 9x_1 + x_2 \leq 10, \quad -5x_1 + 3x_2 \leq 3, \\ & x_1 \geq 0, x_2 \geq 0, \end{aligned}$$

Let $v = \max(1 - \mu_1(z_1), 1 - \mu_2(z_2), 1 - \mu_3(z_3))$ and $w = \max(\nu_1(z_1) - 0, \nu_2(z_2) - 0, \nu_3(z_3) - 0)$, then the problem is formulated to be a single objective optimization problem as

$$\min \quad v + w$$

subject to the constraints

$$\begin{aligned} & \{\hat{\mu}_1 - \mu_1(z_1(x))\} \leq v, \quad \{\hat{\mu}_2 - \mu_2(z_2(x))\} \leq v, \quad \{\hat{\mu}_3 - \mu_3(z_3(x))\} \leq v, \\ & \{\nu_1(z_1(x)) - \hat{\nu}_1\} \leq w, \quad \{\nu_2(z_2(x)) - \hat{\nu}_2\} \leq w, \quad \{\nu_3(z_3(x)) - \hat{\nu}_3\} \leq w, \\ & 5x_1 + 7x_2 \leq 12, \quad 9x_1 + x_2 \leq 10, \quad -5x_1 + 3x_2 \leq 3, \\ & x_1 \geq 0, x_2 \geq 0, v \geq 0, w \geq 0, \end{aligned}$$

After simplification, it becomes

Interactive intuitionistic fuzzy technique in multi-objective optimization

$$\begin{aligned}
 &\min \quad v + w \\
 &\text{subject to the constraint} \\
 &1 - ((5x_1 + 5x_2 - 0) / 10) \leq v, \quad 1 - ((6 - 5x_1 - x_2) / 5) \leq v, \\
 &1 - ((3x_1 - 8x_2 + 10) / 10) \leq v, \quad ((10 - 5x_1 - 5x_2) / 12) - 0 \leq w, \\
 &((5x_1 + x_2 - 1) / 7) - 0 \leq w, \quad ((0 - 3x_1 + 8x_2) / 12) - 0 \leq w, \\
 &5x_1 + 7x_2 \leq 12, \quad 9x_1 + x_2 \leq 10, \quad -5x_1 + 3x_2 \leq 3, \\
 &x_1 \geq 0, x_2 \geq 0, v \geq 0, w \geq 0,
 \end{aligned}$$

The solution using Lingo (14.0.1) is obtained as given in Table 3.

4. In order to help the DM to express level of reference for membership and non-membership functions at next level of interaction, DM is requested to select an appropriate standing objective from family the objectives $z_i(x)$, $i = 1, 2, 3$. Suppose DM selects z_3 as appropriate standing objective function. Then for membership level, trade-off information between standing membership function $\mu_3(z_3(x))$ and each of the other membership functions is analytically computed and obtained as

$$\begin{aligned}
 -\frac{\partial \mu_3}{\partial \mu_1} &= -\frac{\partial \mu_3}{\partial z_3} \frac{\partial z_3}{\partial z_1} \frac{\partial z_1}{\partial \mu_1} = -\frac{\partial \mu_3}{\partial z_3} \frac{\partial z_3}{\partial z_1} \left(\frac{\partial \mu_1}{\partial z_1} \right)^{-1} = 43/20 \\
 -\frac{\partial \mu_3}{\partial \mu_2} &= -\frac{\partial \mu_3}{\partial z_3} \frac{\partial z_3}{\partial z_2} \frac{\partial z_2}{\partial \mu_2} = -\frac{\partial \mu_3}{\partial z_3} \frac{\partial z_3}{\partial z_2} \left(\frac{\partial \mu_2}{\partial z_2} \right)^{-1} = 11/8
 \end{aligned}$$

And for non-membership level, trade-off information between standing non membership function $\nu_3(z_3(x))$, corresponding to same objective function $z_3(x)$, and each of the other non-membership functions is analytically computed and obtained as

$$\begin{aligned}
 -\frac{\partial \nu_3}{\partial \nu_1} &= -\frac{\partial \nu_3}{\partial z_3} \frac{\partial z_3}{\partial z_1} \frac{\partial z_1}{\partial \nu_1} = -\frac{\partial \nu_3}{\partial z_3} \frac{\partial z_3}{\partial z_1} \left(\frac{\partial \nu_1}{\partial z_1} \right)^{-1} = 43/20 \\
 -\frac{\partial \nu_3}{\partial \nu_2} &= -\frac{\partial \nu_3}{\partial z_3} \frac{\partial z_3}{\partial z_2} \frac{\partial z_2}{\partial \nu_2} = -\frac{\partial \nu_3}{\partial z_3} \frac{\partial z_3}{\partial z_2} \left(\frac{\partial \nu_2}{\partial z_2} \right)^{-1} = 77/48
 \end{aligned}$$

These trades off rates, for both membership and non-membership functions, together with that Pareto optimal solution are sent to DM.

5. Suppose the decision maker is satisfied; then stop. Otherwise on the basis of supplied information, DM updates the reference levels of membership and non-membership function of standing objective function z_3 as $\mu_3(z_3) = 0.6$ and $\nu_3(z_3) = 0.3$ respectively. The other values of reference membership and non-membership function are obtained from trade off rates as in Table 4.

Then move to step 3. DM should consider the increase rate of satisfaction in terms of the membership degree and decrease rate of satisfaction in terms of non-membership degree such that sum of membership and non-membership degree does not exceed unity. Hence the corresponding problem from step 3 becomes

$$\begin{aligned}
 &\min \quad v + w \\
 &\text{subject to the constraints} \\
 &0.27907 - ((5x_1 + 5x_2 - 0) / 10) \leq v, \quad 0.436364 - ((6 - 5x_1 - x_2) / 5) \leq v, \\
 &0.6 - ((3x_1 - 8x_2 + 10) / 10) \leq v, \quad ((10 - 5x_1 - 5x_2) / 12) - 0.139535 \leq w, \\
 &((5x_1 + x_2 - 1) / 7) - 0.187013 \leq w, \quad ((0 - 3x_1 + 8x_2) / 12) - 0.3 \leq w, \\
 &5x_1 + 7x_2 \leq 12, \quad 9x_1 + x_2 \leq 10, \quad -5x_1 + 3x_2 \leq 3, \\
 &x_1 \geq 0, x_2 \geq 0, v \geq 0, w \geq 0,
 \end{aligned}$$

As before, the solution by Lingo (14.0.1.57) gives the solution set as in Table 5. If the DM updates the reference level of non-membership function for z_3 to be 0.2, then the corresponding problem gives the Pareto optimal solution as given in Table 6. If the DM is satisfied with the current value of membership, non-membership and hence value of objective functions of this Pareto optimal solution, stop. Then the current Pareto optimal solution is the satisfying solution for DM. Otherwise the DM updates the current reference membership level and reference non membership

Interactive intuitionistic fuzzy technique in multi-objective optimization

level for the standing objective function $z_3(x)$ only, by considering the values of the membership functions and non-membership functions together with trade-off rates, such that sum of membership and non-membership grade does not exceed unity in any case and returns to Step 3.

Table 1 Individual minimum and maximum of each objective function

Objective function	Minimum value	Maximum value
Z_1	0	10
Z_2	0	6
Z_3	-11.1	3.333

Table2 Subinterval for membership and non-membership function

Objective function	Value of membership function		Value of non-membership function	
	$\mu_i(z_i) = 0$	$\mu_i(z_i) = 1$	$\nu_i(z_i) = 1$	$\nu_i(z_i) = 0$
Z_1	0	10	-2	10
Z_2	6	1	8	1
Z_3	-10	0	-12	0

Table 3 Solution at stage I

Stage	Optimal values
-------	----------------

I	$x_1^* 0.475$	$\mu_1^*(z_1) 0.586$	$\nu_1^*(z_1) 0.345$	$Z_1^* 5.856$
		$\mu_2^*(z_2) 0.586$	$\nu_2^*(z_2) 0.295$	$Z_2^* 3.072$
	$x_2^* 0.696$	$\mu_3^*(z_3) 0.586$	$\nu_3^*(z_3) 0.345$	$Z_3^* -4.143$

Table 4 Updated reference level for each objective function

Objective function	Z_1	Z_2	Z_3
Membership values	0.279	0.436	0.6
Non membership values	0.139	0.187	0.3

Table 5 Solution at stage II

Stage	Updated reference level		Optimal values			
II (0.3)	$\mu_1(z_1)$	$\nu_1(z_1)$	x_1^* 0.554	$\mu_1^*(z_1)$	$\nu_1^*(z_1)$	Z_1^*
	0.279	0.139		0.631	0.307	6.31
	$\mu_2(z_2)$	$\nu_2(z_2)$		$\mu_2^*(z_2)$	$\nu_2^*(z_2)$	Z_2^*
	0.436	0.187	x_2^* 0.708	0.503	0.354	3.48
	$\mu_3(z_3)$	$\nu_3(z_3)$	0.6	$\mu_3^*(z_3)$	$\nu_3^*(z_3)$	Z_3^*
	0.6	0.3		0.6	0.333	-4

Table 6 Next solution

Stage	Updated references			Optimal values		
II (0.2)	$\mu_1(z_1)$	$\nu_1(z_1)$	x_1^* 0.543	$\mu_1^*(z_1)$	$\nu_1^*(z_1)$	Z_1^*

Interactive intuitionistic fuzzy technique in multi-objective optimization

0.279	0.093		0.623	0.314	6.23
$\mu_{2(z_2)}$	$\nu_{2(z_2)}$	x_2^*	$\mu_{2^*(z_2)}$	$\nu_{2^*(z_2)}$	Z_2^*
0.436	0.124	0.704	0.516	0.345	3.42
$\mu_{3(z_3)}$	$\nu_{3(z_3)}$		$\mu_{3^*(z_3)}$	$\nu_{3^*(z_3)}$	Z_3^*
0.6	0.2		0.6	0.333	-4

In this example, if further iterations are done, the optimal solutions at stage III are obtained as follows:

Table 7 Solution at stage III

Stage	Updated reference level		Optimal values			
III	$\mu_{1(z_1)}$	$\nu_{1(z_1)}$	x_1	$\mu_{1(z_1)}$	$\nu_{1(z_1)}$	Z_1
	0.325	0.093		0.581	0.349	5.814
	$\mu_{2(z_2)}$	$\nu_{2(z_2)}$	0.573	$\mu_{2(z_2)}$	$\nu_{2(z_2)}$	Z_2
	0.509	0.125	x_2	0.509	0.350	3.454
	$\mu_{3(z_3)}$	$\nu_{3(z_3)}$	0.589	$\mu_{3(z_3)}$	$\nu_{3(z_3)}$	Z_3
	0.7	0.2		0.7	0.25	-3

It should be stressed to the DM that any improvement of one membership function can be achieved only at the expense of at least one of other membership functions. If the same problem is solved under simple fuzzy environment, then the optimal solutions are obtained as in Table 8.

Table 8 Solution in classical fuzzy environment

Stage	Updated references	Optimal values
-------	--------------------	----------------

I	$\mu_1(z_1)$	1	x_1	0.475	$\mu_1(z_1)$	0.585	Z_1	5.856
	$\mu_2(z_2)$	1			$\mu_2(z_2)$	0.585	Z_2	3.071
	$\mu_3(z_3)$	1			$\mu_3(z_3)$	0.585	Z_3	-4.143
II	$\mu_1(z_1)$	0.279	x_1	0.042	$\mu_1(z_1)$	0.279	Z_1	2.790
	$\mu_2(z_2)$	0.436			$\mu_2(z_2)$	1	Z_2	0.727
	$\mu_3(z_3)$	0.6			$\mu_3(z_3)$	0.6	Z_3	-4

7 Conclusion:

The concept of interactive intuitionistic fuzzy optimization is introduced and applied here. In interactive fuzzy optimization, for one level of acceptance 0.6 for z_3 , only one optimal solution set $\{z_1 = 2.7907, z_2 = 0.727275, z_3 = -4\}$ is obtained.

But in proposed approach, for same level of acceptance 0.6 for z_3 , different optimal solution sets are obtained corresponding to different rejection levels i.e. under intuitionistic fuzzy environment, more accurate conversion of imprecise linguistic information (as obtained from DM) is used, e.g. for reference non membership level 0.3 of z_3 , optimum value of z_1 is 6.31 and for that of 0.2, it is 6.23. Thus DM may select the solution that best fits his/her aspiration level in IF environment. Therefore this method is more flexible than usual fuzzy interactive method.

Moreover in proposed method, DM supplies reference membership and reference non membership level for one objective on every step. The reference levels (both membership and non-membership) for other objective functions are obtained analytically by using trade off rates. Whereas in simple fuzzy interactive process, DM supplies the reference level for all membership functions at each stage. Thus our method is more analytical in nature. Also, it saves the precious time of DM etc.

Finally, it may be noted that customer (in this case, decision maker) is our king and his/her choice is must be given highest priority in imprecise environment. Till date, there is no standard form of optimization

problem in imprecise environment and it needs to be customized according to requirement. Effort is on to find a concrete and everywhere-accepted format of imprecise real-life optimization problem and a standard solution procedure of it.

References:

- Angelov, P. (1997) 'Optimization in an intuitionistic fuzzy environment', *Fuzzy Sets and Systems*, Vol. 86, pp.299–306.
- Atanassov, K. (1986) 'Intuitionistic fuzzy sets', *Fuzzy Sets and Systems*, Vol. 20, pp.87–96
- Atanassov, K. (1995) 'Ideas for intuitionistic fuzzy sets equations, inequalities and optimization', *Notes on Intuitionistic Fuzzy Sets*, Vol. 1, No. 1, pp.17–24.
- Bellman, R. E., Zadeh, L. A. (1970) 'Decision making in a fuzzy environment', *Management Science*, Vol. 17, pp.B141–B164.
- Ji, S., Li, G., Li, C. (2009) 'Efficient Interactive Fuzzy Keyword Search', *Proceedings of the 18th international conference on World wide web*, 20 –April 2009, Madrid, pp.371-380.
- Mandal, N. K., Roy, T. K. (2011) 'Geometric Programming Approach to an Interactive Fuzzy Inventory Problem', *Advances in Operations Research*, Vol. 2011.
- Sakawa, M. Hitoshi, Y. Yumine, T. (1984) 'An Interactive Fuzzy Satisficing Method for Multiobjective Linear-Programming Problems and Its Application', *IEEE Transactions on Systems, Man and Cybernetics*, Vol. 17, pp.654-661.
- Sakawa M, Hitoshi Yano (1990) *Interactive Decision Making for Programming Problems with Fuzzy Parameters*, ISBN: 978-94-010-7449-0, pp.191-228.
- Sakawa, M., Nishizaki, I., Uemura, Y. (1998) 'Interactive Fuzzy & Programming for Multi-Level Linear Programming Problems', *Computers Mathematics with Applications*, Vol. 36, pp.71-86.
- Zadeh, L. A. (1965) 'Fuzzy sets', *Inf. Control*, Vol. 8, pp.338-353.
- Zimmermann, H. (1978) 'Fuzzy programming and linear programming with several objective functions', *Fuzzy Sets and Systems*, Vol. 01, pp. 45-55.